



Easy Crimp CAT 6_A STP

Description

CCS Easy Crimp shielded plug used to connect cables with solid and flexible conductors.
 With the toolless Easy Crimp system, the connection is always fast and performing.
 Suitable for the realization of the modular plug terminated link (MPTL), "transition point" or patch cords out of the standard lengths.
 Characteristics meet and exceed Cat.6_A - Class E_A requirements according to ISO/IEC 11801 and ANSI/TIA-568.2-D
 Suitable for PoE/PoE+/PoE++ applications

General characteristics

Material	Plug housing in zinc alloy with high mechanical resistance; 8 nickel bronze contacts plated with 50 µm hard gold
Connection	IDC insulation displacement for solid conductors 22-26 AWG and flexible conductors 22-27 AWG; double labelling colour scheme indicating the two T568A/B connections
Installation	On cables with solid and flexible conductors
Compatible cable diameter	From 6 to 9 mm

Performance

Compliance	UL 1863 Communications-Circuit Accessories
Standards	ISO/IEC 11801-1/2:2017 EN 50173-1/2:2018; ANSI/TIA-568.2-D IEC 60603-7-51 IEC 60512-99-002:2019

Code	Description	Packaging
2012009	CAT6A STP Easy Crimp field plug	1 pc